Acoustic characterization of Mutriku OWC Plant



Juan Bald¹, Ainhize Uriarte¹, Pablo Ruiz², Pablo Cervantes², Noelia Ortega²


¹AZTI. Marine Research Division. Pasaia (Gipuzkoa), Spain. *Corresponding author: <u>jbald@azti.es</u>







1. Introduction



The Mutriku Oscillating Water Column (OWC) Plant is an onshore infrastructure for wave energy harnessing promoted by the Basque Entity of Energy (Ente Vasco de la Energía, EVE). The facility is housed within a breakwater at the port of Mutriku (Basque Country, Northern Spain) and opened in July 2011. The plant consists of 16 turbines giving a total installed capacity of 296 kW. During winter 2015 it reached a major milestone; its first GWh of electricity supplied to the grid. This facility is now available as a test site providing developers with a unique opportunity to test new concepts in air turbines, generators, control strategies and auxiliary equipment.




Like other human activities in the marine environment, some environmental impacts over the marine environment were expected during the Mutriku OWC Plant exploitation phase. Among them, the generation of underwater sound during this phase was identified as one of the main expected environmental impact. In order to evaluate this impact, an environmental monitoring Plan (EMP) was developed for the monitoring of the underwater sound produced by the Mutriku OWC Plant.

2. Methodology

Sampling campaign

2 sampling campaigns where undertaken following the methodology developed by the Marine Technology Center (CTN):



The sampling campaign was done with an icListen HF 200 kHz hydrophone of Ocean Sonics.





Data processing

Data processing has been undertaken according to the requirements of the Marine Strategy Framework Directive (MSFD) (Directive 2008/56/CE) and the indicators established according to the Commission Decision 2010/477/UE for the Descriptor 11 of the Directive (Introduction of energy, including underwater noise, is at levels that do not adversely affect the marine environment):

Descriptor 11.1 Distribution in time and place of loud, low and mid frequency impulsive sounds:

Proportion of days and their distribution within a calendar year over areas of a determined surface, as well as their spatial distribution, in which anthropogenic sound sources exceed levels that are likely to entail significant impact on marine animals measured as **Sound Exposure Level (SPL) (in dB re 1 μPa².s)** or as peak sound pressure level (in dBre 1μPa_{peak}) at one metre, measured over the frequency band 10 Hz to 10 kHz.

Descriptor 11.2 Continuous low frequency sound


Trends in the ambient noise level within the 1/3 octave bands 63 and 125 Hz (centre frequency) (re 1 μPa RMS; average noise level in these octave bands over a year) measured by observation stations and/or with the use of models if appropriate.

3. Results

The results obtained with both indicators didn't show any evidence of impulsive neither continuous sound emission coming form the OWC Plant of Mutriku.

The graphic representation of some of the results shown below:


Indicator 11.1 (Impulsive sounds)



However, it's important to underline some limitations in the data:

the time scale of the data series is too short;

the difference in the time scale between samples and between OWC Plant operating and stopped makes difficult the comparison between measures.



4. Conclusions



No evidences of significant acoustic impact coming from the Mutriku OWC Plant were obtained.

ac

Nevertheless, some important limitations related with the design of the EMP suggested the development in the future of a more advanced monitoring strategy based on the implementation of a permanent acoustic underwater monitoring station cabled to the Mutriku OWC Plant.

Acknowledgements



This work has been funded by the **Diputación Foral de Gipuzkoa** under the program for the supporting of the
Science, Technology and Innovation network in Gipuzkoa
2015