

Scottish Marine and Freshwater Science

Volume 6 Number 14

Developing an avian collision risk model
to incorporate variability and uncertainty

Elizabeth Masden

© Crown copyright 2015

Scottish Marine and Freshwater Science Report Vol 6 No 14
Developing an avian collision risk model to incorporate variability and
uncertainty

Elizabeth Masden

Published by Marine Scotland Science

ISSN: 2043-7722

DOI: 10.7489/1659-1

Marine Scotland Science is the directorate of the Scottish Government responsible for the integrated management of Scotland's seas. Marine Scotland Science (formerly Fisheries Research Services) provides expert scientific and technical advice on marine and fisheries issues. Scottish Marine and Freshwater Science is a series of reports that publishes results of research and monitoring carried out by Marine Scotland Science. It also publishes the results of marine and freshwater scientific work that has been carried out for Marine Scotland under external commission. These reports are not subject to formal external peer review.

This report presents the results of marine and freshwater scientific work carried out for Marine Scotland under external commission.

Developing an avian collision risk model to incorporate variability and uncertainty

Elizabeth Masden

Environmental Research Institute
North Highland College – UHI
University of the Highlands and Islands
Thurso, KW14 7EE



Acknowledgements

This project was funded through a NERC knowledge exchange grant (grant number NE/L002728/1). The work was overseen by a project group comprising Aonghais Cook and Lucy Wright (BTO), Ian Davies (Marine Scotland Science), Aly McCluskie (RSPB), Marcus Cross (ScottishPower Renewables), and Kit Hawkins (HiDef Aerial Surveying Limited). However, this document is not officially endorsed by any of these organisations and does not constitute guidance from statutory bodies.

The original R model code from which this model update was developed was written by Aonghais Cook. Seabird data were provided by the RSPB from the FAME project, with particular thanks to Ellie Owen. Many thanks also to those who participated in the stakeholder interviews.

Part 1: Model Description

Background

As wind energy developments increase globally the potential associated environmental impacts are receiving considerable attention, particularly avian impacts. These potential impacts on bird populations can be grouped into three main types: direct mortality due to collision with turbines/infrastructure; physical habitat modification and/or loss; and behavioural responses of birds to turbines (Fox *et al.* 2006; Langston 2013). Focussing on avian collision, a variety of methods have been developed to aid the assessment of the risk of collision, including collision risk models.

After extensively reviewing both the peer-reviewed scientific literature and grey literature, 10 distinct collision risk models referring to birds and wind turbines were identified, the earliest dating back to 1996 (Tucker 1996). At their core, most avian collision risk models include a calculation of the probability of a collision occurring (assuming no evasive action or avoidance behaviour) and often also a measure of the number of birds at risk, if an estimate of likely collision events is to be calculated. The probability of collision is generally based on the probability of a turbine blade occupying the same space as the bird during the time that the bird takes to pass through the rotor swept area. This therefore relies upon information on both bird and wind turbine characteristics such as bird morphometrics and flight speed, turbine rotor speed and size, etc.

In the UK, the most frequently used avian collision risk model is commonly known as 'the Band model' (Band, Madders & Whitfield 2007) and was originally conceived in 1995. Since then it has undergone several iterations with the most recent associated with the Strategic Ornithological Support Services (SOSS) (Band 2012a; b). The Band model (Band 2012b) provides four different options for calculating collision risk.

- Option 1 - Basic model, i.e. assuming that a uniform distribution of flight heights between the lowest and the highest levels of the rotors and using the proportion of birds at risk height as derived from site survey.
- Option 2 - Basic model, but using the proportion of birds at risk height as derived from a generic flight height distribution provided.
- Option 3 - Extended model and using a generic flight height distribution.
- Option 4 - Extended model and using a flight height distribution generated from site survey.

The most recent update of the Band model guidance also provides an approach under which uncertainty can be expressed. However, this approach is relatively simplistic and can only be applied when the sources of variability are independent of one another. Furthermore, although provided, it is not routinely followed and so could

be improved upon. From undertaking interviews with stakeholders (for summary see Appendix 1), it was established that a new collision risk model that was fundamentally different was not required by the industry and the Band model was considered generally fit for purpose. However, although the majority of the stakeholders questioned did not consider major changes necessary, the general opinion was that if it were possible to incorporate uncertainty into the modelling process, it would be beneficial. The main reasoning for this was that expressing collisions as a single number does not sufficiently represent the complexity of the situation. In addition, it is known that the Band model is sensitive to the choice of input parameters (Chamberlain *et al.* 2006). Variability in input parameters such as bird density, flight speed and turbine rotor speed are likely to contribute uncertainty to the final collision estimates. Sensitivity analyses of both the basic and extended options of the Band model are provided in Appendix 2.

General purpose of model update

The general purpose of this collision risk model update is to further develop the application of the Band model using a simulation approach to incorporate variability and uncertainty. In this report we refer to variability as the inherent heterogeneity of the environment and uncertainty as a lack of data or incomplete knowledge. The simulation model randomly samples from distributions for each of the model parameters and the simulations can then be used to derive average collision estimates, with associated confidence intervals. The model update will therefore allow for a better understanding of the uncertainty associated with the predicted collision impact of a wind farm development and provide confidence limits, something which has previously been absent. In addition, the incorporation of uncertainty would reduce the possibility that a collision estimate was driven by the choice of a single input parameter value. Ultimately, the update should aid streamlining of the planning/consenting stages of a development by providing information not only on the magnitude of collisions i.e. the number of collision events, but also the likelihood of that number of collisions occurring.

In this model update, variability and uncertainty are considered together in combination, rather than separately. Some model input parameters will have associated variability, for example bird body length, others may be expected to be point estimates with associated uncertainty, such as turbine rotor radius, and some parameters may have both variability and uncertainty. Ideally it would be possible to differentiate between variability and uncertainty but at present this is not possible due to a lack of data. However, including variability and uncertainty in combination in the model still provides a significant step forward.

The report describes the data required, and the methods used, to estimate collision risk. It is accompanied by a worked example and R code (available at <http://dx.doi.org/10.7489/1657-1>), which enables the collision risk calculations to be performed in a standardised and reproducible way.

Model format

Whereas previous iterations of the Band model have used Microsoft Excel, the collision risk model updated presented uses R <http://www.r-project.org>. Opinions given during stakeholder interviews (for summary see Appendix 1) were that the Excel spreadsheet was difficult to use at times and there was the potential for errors to be easily introduced into calculations, particularly if the spreadsheet did not update correctly when new input parameters were entered. In addition, the Excel spreadsheet does not allow results to be reproduced easily making auditing onerous, as values have to be entered manually for each occasion or scenario. Using R enables reproducible methods and results as code and data are provided along with the computational environment used. This improves understanding and allows verification of results, therefore increasing transparency.

Relationship to previous guidance on collision risk modelling

The model described and presented in this document is an update to the Band collision risk model (Band 2012b) which was most recently updated as part of SOSS. The mechanistic details of the Band model have not been altered and form the core of the model update described below.

The guidance (Band 2012b) states clearly that the collision estimate should be a best-estimate rather than a worst-case scenario.

“This guidance does not recommend use of ‘worst case’ assumptions at every stage. These can lead to an overly pessimistic result, and one in which the source of the difficulty is often concealed. Rather, it is recommended that ‘best estimates’ are deployed, and with them an analysis of the uncertainty or variability surrounding each estimate and the range within which the collision risk can be assessed with confidence. In stating such a range, the aspiration should be to pitch that at a 95% confidence level, that is, so that there is 95% likelihood that the collision risk falls within the specified range. However, given the uncertainties and variability in source data, and the limited firm information on bird avoidance behaviour, it seems likely that for many aspects the range of uncertainty may have to be the product of expert judgement, rather than derived from statistical analysis.”

The model update presented in this document follows this principle by using ranges of values rather than a single, ‘worst-case’ scenario.

The previous guidance (Band 2012b) presented a method to express overall uncertainty in collision estimates (stage F), as there are a large number of sources of variability or uncertainty. Cook *et al.* (2012) and Johnston *et al.* (2014) are key resources to include in this process as they provide data with confidence limits. However, the uptake of stage F in the collision estimation process appears to have been minimal. There have also been cases of its misapplication with estimates presented with implausible confidence limits such as 40 ± 100 collisions, suggesting

that negative numbers of collisions are possible. In addition, the method for expressing uncertainty suggested in stage F does so *post hoc*, rather than being integrated in to the model itself. Also, combining sources of uncertainty as suggested is only applicable when parameters are independent. The model update described in this document further develops the concepts presented in stage F of the previous guidance.

Before the most recent iteration of the Band model (Band 2012b) was conceived, McAdam (2005) produced a model which incorporated species specific flight height distributions. Variation in flight height has now been incorporated in to the most recent update (Band 2012b), however, the model produced by McAdam (2005) used Monte Carlo simulation to obtain 500 samples. Using Monte Carlo methods allowed for the production of summary statistics rather than single collision estimates, as well as probability distributions of events (numbers of collisions) occurring. It was also executed using R rather than Excel. In the model update presented below, the method of Monte Carlo simulation used by McAdam (2005) has been applied to the most recent version of the Band model to allow the incorporation of uncertain parameter values.

General data requirements

The model update is based on the Band model (Band 2012b) therefore the types of data required are the same:

- Bird survey – data on the number of birds flying through or around the site, and their flight height
- Bird specification – details on bird morphology and flight speed
- Turbine specification – details on the number, size and rotation speed of turbine blades
- Bird behaviour – prediction of likely change due to wind farm, e.g. avoidance

The crucial difference from previous iterations of the Band model is that rather than using a single value for a given input parameter, for example bird flight speed, this update of the model randomly samples from a distribution of values. Using the randomly sampled parameter values, a collision risk estimate is calculated. This process is then repeated numerous times to produce a distribution of collision estimate for which summary statistics i.e. average and spread, can be calculated. Whereas the previous guidance and methods provided a measure of uncertainty *post hoc*, uncertainty is now incorporated in the modelling procedure itself with this update. Therefore, information regarding uncertainty in the data is required to be entered into the model.

Where possible, and when suitable, a mean and standard deviation should be provided for input parameters. These should capture the uncertainty within the data. For example, if the maximum turbine blade width has not been decided upon but is likely to be 5 metres then a mean = 5 should be provided with a standard deviation

which describes the uncertainty and possible values. For this example, a mean of 5 and standard deviation of 0.3 would give a minimum of approximately 4 metres, and a maximum of approximately 6 metres. If there is no uncertainty and it is definite that the maximum blade width is to be 5 metres then a value of 5 should be entered as the mean and either 0 entered as the standard deviation or it left blank.

To incorporate uncertainty into the collision risk estimate, a mean and standard deviation will be required for the following parameters. Attention should be paid to the units of measure.

Table 1: Bird-related parameters

Parameter	Units	Description/Notes
Length	m (metres)	
Wingspan	m (metres)	
Flight speed	m/sec	Available from telemetry data or wind tunnel experiments
Flight type		Flapping or gliding
Nocturnal activity	Proportion e.g. 0.5 for 50%	Available from telemetry data or visual observations
Proportion at collision risk height	Proportion e.g. 0.5 for 50%	
Flight height distribution	Proportion e.g. 0.5 for 50%	Distribution curves from which the proportion of birds flying within 1 metre height bands are calculated. Data provided by BTO (Johnston <i>et al.</i> 2014). (See below)
Avoidance rate	Proportion e.g. 0.5 for 50%	Suggested values available from MSS avoidance report
Bird density	Birds/km ²	Birds in flight in daytime, taken from survey data

Table 2: Turbine-related parameters

Parameter	Units	Description/Notes
Rotor radius	m (metres)	Measured from the axis of rotation to blade tip.
Hub height	m (metres)	Sum of rotor radius and minimum blade clearance above HAT. (See below)
Max. blade chord width	m (metres)	
Rotation speed	rpm	See below
Blade pitch	Degrees relative to rotor plane	See below
Turbine operation time	Proportion e.g. 0.5 for 50%	Requires both information on wind availability and maintenance down time.

This model requires information on flight height distributions, if options 2, 3 or 4 are to be used. A generic flight height distribution is presented with the SOSS guidance (Band 2012a; b; Cook *et al.* 2012), however this does not provide information on the uncertainty associated with the distribution. Johnston *et al.* (2014) used a bootstrapping technique to provide confidence limits associated with the generic flight distribution and these bootstraps can be used within this model update to provide uncertainty associated with the flight height distribution curve. For each iteration of the model, a curve produced from a bootstrap sample is re-sampled and used. It is possible to use this update to calculate a collision risk estimate using option 4, should site-specific data on flight height distributions be available.

The model also requires information on wind speed ($m.s^{-1}$) at the proposed site as well as the relationship between rotor speed and wind speed and turbine pitch and wind speed. This allows rotor speed and pitch to be linked both to the wind speed and also to each other. This is achieved through the provision of data similar to that in table 3 (below), describing the relationship between wind speed and rotor speed and pitch, as well as information on wind speed at the site.

Table 3: Example data describing relationship between wind speed, rotor speed and blade pitch.

Wind speed (m/s)	Rotor Speed (rpm)	Pitch (degrees)
0	0	90
1	0	90
2	0	90
3	6	0
4	6	0
5	6	2
6	8	4
...

The turbine operation time is wind availability minus maintenance down time. Wind availability should be provided as a constant i.e. proportion of time the wind conditions allow for turbine operation and should be available from meteorological data. Maintenance time should be provided as a monthly mean and standard variation as it is expected that there will be uncertainty and variability surrounding maintenance.

Hub height is the distance from highest astronomical tide (HAT) to the axis of rotation of the turbine. This distance comprises the rotor radius and the distance between the minimum rotor tip height and HAT. Therefore, as rotor radius is already entered into the model, it is importantly only the distance component from HAT to the minimum rotor height that is required here and not the total hub height.

Calculating collision risk

As stated previously, this model is an update of the Band model. For more information on the Band model refer to (Band 2012a; b) and associated information on the SOSS website <http://www.bto.org/science/wetland-and-marine/soss/projects>.

Monte Carlo simulation

The model update presented herein uses Monte Carlo simulation. Monte Carlo simulation is a computational technique that uses random sampling to produce numerical results, and in this model update, is used to obtain values for uncertain input parameters, for example flight speed or bird length. These values are then used in the Band model. For each set of random samples, a collision estimate is calculated. Therefore if the simulation is run for 100 iterations, 100 sets of random

input parameters will be sampled and 100 collision risk estimates calculated, instead of a single value. Monte Carlo simulation therefore allows for the presentation of a range of possible outcomes, when there is uncertainty surrounding the input data, and produces distributions of possible collision estimates. The distribution data can then be further re-sampled and used in stochastic population models, should this be required.

Sampling distributions

With the exception of rotor speed, pitch and flight height distributions, input values for the Band model are sampled from probability distributions. These distributions are parameterised using data provided by the user and have been constrained to the Normal distribution, or in cases where negative values are not plausible, the truncated Normal distribution. The user defines the mean or expected value and a standard deviation to describe the variation about the mean. Values in the middle near the mean are most likely to occur. The decision to use the Normal distribution was made on the basis of ease of parameterisation for the user as well as suitability. The Normal distribution was considered more suitable than a uniform distribution because in most cases it is expected that there will be a more likely value, and the uniform distribution, where all values are equally likely, would therefore enter more uncertainty than realistic into the model. It is however accepted that in all cases, the Normal distribution may not be the most suitable distribution, but there is a balance to be achieved between suitability and ease of use.

Collision risk options

The Band model provides four different options for calculating collision risk (Band 2012b). Options 1, 2 and 3 are the most frequently used. The model update calculates estimates for both the basic (options 1 and 2) and extended (option 3) versions of the Band model. It is possible to use this update to calculate a collision risk estimate using option 4, should site-specific data on flight height distributions be available. However, this would require a large amount of data collection, to provide information on variation in flight height distribution therefore the default option does not include option 4.

Running the model

As well as being designed to run numerous simulations of the Band model, this update is designed to loop through multiple species and multiple turbine designs automatically. Therefore once the initial user information is entered and the model begins, the user is not required to enter any further information and the results will be saved automatically to the location specified by the user. The number of results obtained will depend on the number of different turbine designs and species entered.

Model Output

The model outputs information on the expected numbers of collisions. The information is provided both as tables and figures. Descriptions of the outputs are listed below and illustrated examples are provided in the worked example.

TABLES

1. Overall summary table of collisions by species, turbine and model option. Results are presented as mean, standard deviation (SD) and coefficient of variation (CV), and median and inter quartile range (IQR).
2. Monthly summaries of collisions. Separate tables are produced according to species, turbine and model option for example 6_Black_legged_Kittiwake_monthlySummaryOpt3.csv. Results are presented as mean, standard deviation (SD) and coefficient of variation (CV), and median and inter quartile range (IQR).
3. Summary of sampled bird parameters by species, turbine and model option presented as mean and standard deviation (SD), and median and inter quartile range (IQR).
4. Summary of sampled turbine parameters by species, turbine and model option presented as mean and standard deviation (SD), and median and inter quartile range (IQR).

FIGURES

1. 3-panel boxplots of monthly collisions for model options 1, 2 and 3 by species, and turbine type.
2. Density plots of numbers of collisions by species, and turbine type. A density curve is plotted for each of the 3 model options.
3. If 2 or more turbine models are included, then a 3-panel figure will be produced for each species, with the panels representing model options 1, 2 and 3 and each panel containing density plots for the different turbines included.

In addition to the collision estimates, the model also saves a copy of the input files which were entered into the model, as well as a summary of the randomly sampled input parameter values. This would therefore allow for the model to be re-run and results verified (if required). It also outputs a text file stating the time elapsed between the start and the end of the model, the number of iterations, the species for which the model was run and also the different turbines i.e. 6MW, 8MW, etc. if more than one turbine type was specified.

Future work

During this project, an update to the Band collision risk model (Band 2012b) has been developed, however it is accepted that there are still aspects which could be

improved further in the future with additional updates, particularly with improved data collection methods and understanding of the interactions between birds and wind farms. These are listed below.

1. Wind speed data: This model update has taken a step forward from previous iterations of the Band model by including the relationship between wind speed data and both rotor speed and rotor pitch, however there are still improvements which could be made. Due to a lack of clarity in the availability and format of site-specific wind speed data which is available to developers it was decided that in this model update, wind speed would be sampled from a truncated Normal distribution, parameterised by a mean and standard deviation set by the user. In the future, if consensus could be reached on wind data availability and format, a summary of the raw wind speed data could be used, rather than using it to parameterise a sampling distribution. If this were the case, then it would also be possible to programme the model to automatically calculate wind availability from the wind speed data, rather than this being entered manually.

2. Monthly vs. annual input parameters: The current model uses annual estimates for the majority of input parameters such as bird flight speed and percentage of nocturnal activity. It is possible that these may differ between the breeding and non-breeding season, and vary monthly, and in response to wind speed. However, at present it was considered that data of sufficient quality were not available for enough parameters on a monthly basis to warrant including this in the model for all. Should this be the case, including monthly values for all parameters could introduce unrealistic precision into the model; therefore only monthly values were included for bird density and turbine operation time. In the future it might be more appropriate to consider all input parameters on a monthly basis.

3. Linking wind speed and flight speed: Within this model update bird flight speed was not linked to wind speed. This alteration could improve the model, however little data is available regarding bird flight speeds, especially in relation to wind speed, though more flight speed data are becoming available as the number of projects using telemetry e.g. GPS tags, increases. The link between flight speed and wind speed was however included in the model produced by McAdam (2005), therefore it would be possible to include this relationship in future updates, should sufficient data become available.

4. Validate the model: Due to the difficulties associated with collecting collision data offshore, as yet, it has not been possible to validate this model update. This is the case for previous versions of the Band model and also collision risk models in general. In the guidance supplied alongside the 2012 update to the Band model, Band (2012b) highlights that there is likely to be uncertainty as a result of simplifications in the model itself. As an estimate, it is suggested that this may be in the region of 20%. By using the results of projects, such as the bird collision avoidance component of the Offshore Renewables Joint Industry Programme

(ORJIP) in the UK, to validate the model, it may be possible to quantify this uncertainty more accurately and reduce it through further refinements to the model.

5. Sensitivity analysis: Whilst it is possible to perform a manual sensitivity analysis on the model update (results available in Appendix 2), it would be useful in the future to have the utility to perform a sensitivity analysis as a matter of course during the assessment of collision risk. This would offer users the ability to highlight which parameters had the strongest influence on the final collision estimates and consider how best to target data collection in order to reduce uncertainty. It may also enable developers to plan mitigation strategies, for example by demonstrating how using fewer, larger turbines may reduce collision risk.

Part 2: Worked Example

Downloading R

Whereas previous iterations of the Band model have used Microsoft Excel, the collision risk model update presented uses R. To get the most recent version of R, go to the R website <http://www.r-project.org> and click the 'CRAN' link on the left hand side. Select a mirror site near you from the list provided, click the 'Windows' link on the next page, then the 'base' link on the following page, and then download the R installer from the link 'Download R 3.1.2 for Windows' (note that the version number you see may be different than this example).

The collision risk model (available at <http://dx.doi.org/10.7489/1657-1>) requires the installation of an R package “msm” to allow sampling from a truncated normal distribution. This should be installed before the model is run.

To install the required package type the following

```
install.packages("msm")
```

into the R console and press return.

Once installed, this step should not be required again and the package will be loaded from within the model script.

Imagined scenario

This example is fictitious. The results are not characteristic of collision risks at any particular site.

A wind farm is planned for the North Sea. The imagined area has a width of 10 km and it is intended that the planned wind farm will generate 600MW. The location of the development area is at 55.8 degrees latitude and has a tidal offset of 2.5 metres. One of the seabirds present at the site and considered sensitive to collision risk is the black-legged kittiwake (*Rissa tridactyla*). This worked example estimates a collision risk estimate for kittiwake.

The wind farm is still in the design phase and there is some uncertainty surrounding the turbine design.

The collision risk model

The collision risk model update is provided as R code. The majority of the model is written as functions which are provided in individual files in a folder named 'scripts'. These files do not need to be altered. In terms of code, the ONLY file that needs to

be altered in order to run the collision risk model is "BandModel.R". All other files are called from R within this script.

In addition to a folder called 'scripts' and the code BandModel.R, there should also be a folder named 'data' that contains the data files required to run the model. The folder should contain the following:

*BirdData.csv - contains the biometric & flight speed data for species of interest. At present data for 12 species are included (Fulmar, Gannet, Lesser Black-backed Gull, Herring Gull, Great Black-backed Gull, Black-legged Kittiwake, Guillemot, Razorbill, Little Auk, and Puffin)

Species can be added as required, however, it is not necessary to remove data for species which are not being considered. It is important that the species names used are taken from the file BirdData.csv and are used throughout, otherwise the model will not recognise the species. The species names used in the code are as follows:

Species (scientific name)	Code name used in model
Fulmar (<i>Fulmarus glacialis</i>)	Northern_Fulmar
Gannet (<i>Morus bassanus</i>)	Northern_Gannet
Lesser Black-backed Gull (<i>Larus fuscus</i>)	Lesser_Black_Backed_Gull
Herring Gull (<i>Larus argentatus</i>)	Herring_Gull
Great Black-backed Gull (<i>Larus marinus</i>)	Great_Black_backed_Gull
Black-legged Kittiwake (<i>Rissa tridactyla</i>)	Black_legged_Kittiwake
Guillemot (<i>Uria aalge</i>)	Common_Guillemot
Razorbill (<i>Alca torda</i>)	Razorbill
Little Auk (<i>Alle alle</i>)	Little_Auk
Puffin (<i>Fratercula arctica</i>)	Atlantic_Puffin
Arctic skua (<i>Stercorarius parasiticus</i>)	Arctic_Skua
Great skua (<i>Stercorarius skua</i>)	Great_Skua

*CountData.csv - count data for the species of interest, should be entered as densities (Birds/km²). Make sure that biometric data for each species included here is available in BirdData.csv

*FlightHeight.csv - modelled flight height distributions for 21 species of seabird/seaduck etc. taken from Johnston *et al.* (2014)

*TurbineData.csv - should contain information on the size etc. of the turbines being considered. Each row represents a different turbine model to be considered. The name should be the MW rating of the turbine.

* [insert species name]_ht.csv – should contain bootstrapped flight height distribution data from Johnston *et al.* (2014) for the species required. A separate file is required for each species.

* windpower_[insert turbine model name].csv – should contain the relationship between wind speed, rotor speed and pitch. A separate file is required for each turbine model/type.

Data requirements

BIRD DATA: these data are entered in to BirdData.csv

Bird length (Body_Length, Body_LengthSD): the bird body length data were taken from the Concise Birds of the Western Palearctic (OUP, 1994), BTO bird facts and other sources. A mean and standard deviation were estimated from these sources. Mean = 0.39 metres, standard deviation = 0.005.

Wing span (Wingspan, WingspanSD): the wing span data were taken from the Concise Birds of the Western Palearctic (OUP, 1994), BTO bird facts and other sources. A mean and standard deviation were estimated from these sources. Mean = 1.08 metres, standard deviation = 0.04.

Flight speed data (Flight_Speed, Flight_SpeedSD): the flight speed data used in this worked example were taken from the RSPB FAME project and were collected using GPS tags. The data were used to parameterise a normal distribution. A mean flight speed for each tagged bird was estimated (to remove variation within individual) and then an overall mean of these values was calculated. Mean = $7.26 \text{ m}\cdot\text{s}^{-1}$, standard deviation = 1.5.

Nocturnal activity (Nocturnal_Activity, Nocturnal_ActivitySD): the data used in this worked example to estimate the proportion of nocturnal activity were taken from the RSPB FAME project and were collected using GPS tags. All records away from the nest and travelling at speeds considered to be flying were used. The data were used to parameterise a normal distribution. Mean = 0.033, standard deviation = 0.0045.

Proportion at collision risk height (Prop_CRH_Obs, Prop_CRH_ObsSD): these data are required for the basic model (option 1). A mean and standard deviation were calculated using the data within Black_legged_Kittiwake_ht.csv. For each bootstrapped distribution curve, the proportion of birds between the average minimum and average maximum rotor tip height was summed. From these values, a mean and standard deviation was calculated. Mean = 0.06, standard deviation = 0.009.

Avoidance (AvoidanceBasic, AvoidanceBasicSD, AvoidanceExtended, AvoidanceExtendedSD): This is the probability that a bird on a collision course with a turbine will take evading action to avoid collision. The data were taken from Cook *et al.* (2014) and for kittiwake, we used the ‘all gulls’ avoidance rate. The avoidance rate differs between the basic and extended models and a mean and standard deviation are required for both. Mean (basic) = 0.9893 and standard deviation (basic) = 0.0007; mean (extended) = 0.9672 and standard deviation (extended) = 0.0018.

COUNT DATA: these data are entered in to CountData.csv and are the number of birds in flight in the daytime presented as birds/km². A mean and standard deviation are required. For this worked example, data were taken from the Creyke Beck A Environmental Statement.

Month	Mean	SD
Jan	0.97	0.67
Feb	1.04	0.75
Mar	1.15	0.78
Apr	0.48	0.36
May	0.56	0.58
Jun	0.63	0.45
Jul	0.68	0.47
Aug	0.64	0.47
Sep	0.53	0.39
Oct	1.20	0.78
Nov	1.02	0.61
Dec	0.99	0.7

FLIGHT HEIGHT DISTRIBUTION DATA: these data are contained within FlightHeight.csv and the individual species files such as Black_legged_Kittiwake_ht.csv and are required for options 2 and 3. The data within FlightHeight.csv are provided by the British Trust for Ornithology (Johnston *et al.*, 2014) and are generic flight height distributions. The file provides data on the proportion of birds within 1m height bands for 21 species. For example,

Height (m)	Black_legged_Kittiwake
1	0.089904
2	0.081107
3	0.072538
4	0.067068
5	0.061008
6	0.055579
7	0.050707
...	...

Confidence intervals were calculated around these best fit/generic flight height distributions using a bootstrapping approach, randomly sampling from the original dataset each time. These bootstraps are provided for each species in separate files, for example Black_legged_Kittiwake_ht.csv and are used to include uncertainty surrounding the flight height distribution.

TURBINE DATA: these data are entered into TurbineData.csv and are also contained within the turbine-specific files such as windpower_6. Names in parentheses are the names in the data files and scripts.

Rotor radius (RotorRadius, RotorRadiusSD): this is measured from the axis of rotation to blade tip and was taken from expert opinion. Mean = 80 and Standard deviation = 5

Hub height (HubHeightAdd, HubHeightAddSD): This is the measure that in addition to rotor radius sums to give the distance from HAT to the axis of rotation and was taken from expert opinion. Mean = 26.5 and Standard deviation = 2.

Maximum blade chord width (BladeWidth, BladeWidthSD): This is the maximum width of the rotor blade and was taken from expert opinion. Mean = 5.5 and Standard deviation = 0.3.

Turbine operation time (example for January is JanOp, JanOpMean, JanOpSD): This included both information on wind availability (JanOp) which is considered a constant and maintenance down time (JanOpMean, JanOpSD) which included uncertainty. Data were taken from the Inch Cape Environmental Statement.

Month	Wind availability	Mean maintenance	SD maintenance
Jan	96.28	6.3	2
Feb	96.53	6.3	2
Mar	95.83	6.3	2
Apr	92.78	6.3	2
May	90.86	6.3	2
Jun	92.22	6.3	2
Jul	89.11	6.3	2
Aug	89.92	6.3	2
Sep	93.71	6.3	2
Oct	96.14	6.3	2
Nov	97.14	6.3	2
Dec	96.41	6.3	2

Rotation speed (RotationSpeed, RotationSpeedSD): It is possible to specify a mean rotor speed and standard deviation, however the default model uses the relationship between wind speed and rotor speed provided to calculate the specific rotor speeds, therefore RotationSpeed and RotationSpeedSD in TurbineData.csv should be left blank. The relationship should be provided in a csv file named windpower_[insert model name here] for example windpower_6.csv

The table below shows an example relationship between wind speed, rotor speed and pitch. It was constructed using expert opinion as an example table and used within this worked example. It does not relate to a specific turbine specification currently available.

Wind speed (m/s)	Rotor Speed	Pitch
0	0	90
1	0	90
2	0	90
3	6	0
4	6	0
5	6	2
6	8	4
...

Blade pitch (Pitch, PitchSD): As for rotor speed, it is possible to specify a mean pitch and standard deviation, however the default model uses the relationship between wind speed and pitch provided to calculate the specific rotor pitch, therefore Pitch and PitchSD in TurbineData.csv should be left blank. The relationship should be provided in a csv file named windpower_[insert model name here] for example windpower_6.csv (as above).

Model set up

Before the model can be run it requires information to be entered into the file "BandModel.txt".

1. Set working directory

First, set the working directory. This is the location where the folders 'scripts' and 'data' have been saved as well as 'BandModel.R'. For example,

```
setwd("F:\\BAND CRM For R")
```

This step directs R to all the files and data that are required to run the model therefore all the files required must be within this directory.

2. Set results folder

The model will save output to a folder. Set the name of the results folder, for example, the name of the development. For example,

```
results_folder <- "windfarm1"
```

If no name is specified the model will default to the date. WARNING: If the model is run several times on the same day and no folder name is specified, it will over-write files in the folder.

3. Set model components

Next set the model components. These include:

The number of iterations the model simulation will execute, for example 1000

```
iter<- 1000
```

The species to include, for example kittiwake

```
CRSpecies = "Black_legged_Kittiwake"
```

If more species were to be included this would look like

```
CRSpecies = c("Black_legged_Kittiwake", "Northern_Gannet", "Arctic_Skua")
```

The target power (in MW) to be generated within wind farm, for example 600MW. This is used in conjunction with the turbine name i.e. 6 if a 6MW turbine, to calculate the number of turbines in the array.

```
TPower = 600
```

Large array correction (Yes/No), for example

```
LargeArrayCorrection = "yes"
```

The wind farm width (km), for example 10km

```
WFWidth = 10
```

The proportion of bird flights up/downwind, for example 50%

```
Prop_Upwind = 0.5
```

The latitude of the wind farm in decimal degrees, for example 55.8 degrees. This is used to calculate day length at the site location throughout the year.

```
Latitude = 55.8
```

The tidal offset in metres (to correct for flight heights being calculated in relation to mean sea-level and turbine dimensions being calculated in relation to Highest Astronomical Tide), for example 2.5 metres

```
TideOff = 2.5
```


4. Parameterise wind speed sampling distribution

The model uses wind speed data to calculate rotor speed and pitch. Wind speed data are therefore required. At the time of production it was unclear what format wind speed data would be available to wind farm developers. To avoid inconsistencies, the model samples wind speed from a truncated normal distribution parameterised by the user. The mean wind speed ($\text{m}\cdot\text{s}^{-1}$) and standard deviation are required to be set, for example

```
windSpeedMean<- 7.74  
windSpeedSD<- 3.2
```

It is expected that these will be obtained from met mast data or other sources of wind speed data such as NASA's Modern-Era Retrospective Analysis for Research and Applications (MERRA).

5. Running the model...

Once you have set the working directory and entered all of the necessary information, all that is needed to run the model is to copy and paste all of BandModel.R into the R console, or alternatively type

```
source("*****EnterMyDirectoryHere*****\BandModel.R")
```

in the R console, and press return.

The code is designed to loop through multiple species and multiple turbine designs in a single step. The number of results obtained will depend on the number of different turbine designs entered in TurbineData.csv and the number of different species for which data are entered and listed.

A progress bar will provide an indication of progress and at the end of the model, the time elapsed since the model was started will be displayed.

Model Output

The model outputs information on the expected numbers of collisions. The information is provided both as tables and figures, and according to the species and turbine designs entered into the model. Results are provided for the basic (options 1 and 2) and extended (option 3) versions of the model.

- Option 1 - using the basic model, i.e. assuming that a uniform distribution of flight heights between the lowest and the highest levels of the rotors and using the proportion of birds at risk height as derived from site survey.
- Option 2 - again using the basic model, but using the proportion of birds at risk height as derived from the generic flight height distribution provided.
- Option 3 - using the extended model and using the generic flight height distribution.

Tables

The file names of the tables indicate the type of information contained.

1. CollisionEstimates.csv: Overall summary table of collisions by species, turbine and model option. Results are presented as mean, standard deviation (SD) and coefficient of variation (CV), and median and inter quartile range (IQR).

Species	Turbine	Option	Mean	SD	CV	Median	IQR
Black_legged_Kittiwake	6	1	45.6455	12.5448	27.4831	45.1206	16.5493
Black_legged_Kittiwake	6	2	42.4292	14.5621	34.3210	40.3032	18.671
Black_legged_Kittiwake	6	3	35.4131	13.1271	37.0685	33.0278	16.466

2. 6_Black_legged_Kittiwake_monthlySummaryOpt1.csv : monthly summaries of collisions. Separate tables are produced according to species, turbine and model option. Results are presented as mean, standard deviation (SD) and coefficient of variation (CV), and median and inter quartile range (IQR).

Month	Mean	SD	CV	Median	IQR
Jan	3.080382	1.753642	56.92937	2.970413	2.441757
Feb	3.590156	2.012736	56.06263	3.439408	3.043374
Mar	4.884338	2.76244	56.55711	4.716011	4.134139
Apr	2.890070	1.763726	61.02710	2.648057	2.297968
May	4.255352	2.845274	66.86343	3.771635	3.664073
Jun	4.458946	2.63927	59.19044	4.172458	3.708436
Jul	4.529034	2.769847	61.15756	4.132559	3.751684
Aug	4.034511	2.423247	60.06296	3.738152	3.239942
Sep	2.720596	1.625044	59.73115	2.546583	2.131306
Oct	4.650331	2.451314	52.71267	4.471203	3.288374
Nov	3.484131	1.787375	51.30045	3.386141	2.557487
Dec	3.067742	1.625422	52.98432	2.964345	2.258359

3. 6_Black_legged_Kittiwake_sampledBirdParameters.csv: Summary of sampled bird parameters by species, turbine & model option presented as mean & standard deviation (SD), and median & interquartile range (IQR).

Parameter	Mean	SD	Median	IQR
AvoidanceBasic	0.989328	0.000696	0.989341	0.000986
AvoidanceExtended	0.967215	0.00176	0.967172	0.00244
WingSpan	1.079481	0.040021	1.078701	0.054751
BodyLength	0.3898	0.005124	0.389929	0.007007
PCH	0.06006	0.009073	0.06025	0.012644
FlightSpeed	7.242055	1.472594	7.200565	1.91039
NocturnalActivity	0.033239	0.004627	0.033195	0.005833




4. 6_Black_legged_Kittiwake_sampledTurbineParameters.csv: Summary of sampled turbine parameters by species, turbine and model option presented as mean and standard deviation (SD), and median and inter quartile range (IQR).

Parameter	Mean	SD	Median	IQR
RotorSpeed	7.8795	1.187502	6.8	2.3
RotorRadius	80.02557	4.641109	79.93026	6.275585
HubHeight	106.5836	4.981272	106.4803	6.57322
BladeWidth	5.492034	0.293631	5.499434	0.414762
Pitch	1.091	2.912594	0	0
JanOp	90.04184	1.992513	90.08147	2.699385
FebOp	90.32209	2.00625	90.27184	2.864814
MarOp	89.53487	1.983321	89.52079	2.567127
AprOp	86.5725	2.050986	86.58052	2.786068
MayOp	84.5539	1.99842	84.5696	2.744052
JunOp	86.04224	2.070166	86.06471	2.915727
JulOp	82.7399	2.025924	82.68036	2.643739


AugOp	83.69396	2.0276	83.71622	2.59691
SepOp	87.46471	2.045078	87.38634	2.880023
OctOp	89.81123	1.95635	89.78423	2.731423
NovOp	90.89083	1.979187	90.93791	2.677976
DecOp	90.04899	2.107647	90.1124	2.786412

Figures


1. 6_Black_legged_Kittiwake .jpg: 3-panel boxplots of monthly collisions for model options 1, 2 and 3 by species, and turbine type (included in the file name).



2. 6_Black_legged_Kittiwake_density.jpg: Density plots of numbers of collisions by species, and turbine type (specified in file name). A density curve is plotted for each of the 3 model options.



3. Black_legged_Kittiwake.jpg: If 2 or more turbine models are included, then a 3-panel figure will be produced for each species, with the panels representing model options 1, 2 and 3 and each panel containing probability density plots for the different turbines.



In addition to the collision estimates, the model also saves a copy of the input files which were entered into the model, as well as a summary of the randomly sampled input parameter values. This would therefore allow for the model to be re-run and results verified (if required). It also outputs a text file (run.time.txt) stating the time elapsed between the start and the end of the model, the number of iterations, the species for which the model was run and also the different turbines i.e. 6MW, 8MW, etc. if more than one turbine type was specified.

```
Time difference of 1.936949 hours
"The model ran 1000 iterations"
"The following species were modelled:"
  "Black_legged_Kittiwake"
"The following turbines were modelled:"
  6 8
```

A note on comparisons of results: Whilst differences in the density curves (specifically the spread) can be compared within each model option, they should not be compared between different model options. This is because of differences in the way in which variation and uncertainty are introduced into each model option. For example, in the basic model (options 1 & 2) uncertainty in the proportion of birds at risk height is only introduced when estimating the flux rate. However, in the extended model (option 3), the uncertainty in the flight height distribution is introduced when calculating the collision integral (the extended model equivalent of the probability of collision).

References

- Band, B. (2012a) *Using a Collision Risk Model to Assess Bird Collision Risks for Offshore Windfarms - with Extended Method: Worked Example*.
- Band, B. (2012b) Using a collision risk model to assess bird collision risks for offshore windfarms. *SOSS report, The Crown Estate*.
- Band, W., Madders, M. & Whitfield, D.P. (2007) Developing field and analytical methods to assess avian collision risk at wind farms. (eds M. De Lucas, G.F.E. Janss & M. Ferrer), Quercus, Madrid.
- Chamberlain, D.E., Rehfisch, M.R., Fox, A.D., Desholm, M. & Anthony, S.J. (2006) The effect of avoidance rates on bird mortality predictions made by wind turbine collision risk models. *Ibis*, **148**, 198–202.
- Cook, A.S.C.P., Johnston, A., Wright, L.J. & Burton, N.H.K. (2012) A Review of Flight Heights and Avoidance Rates of Birds in Relation to Offshore Wind Farms. *BTO Research Report 618*, 1–61.
- Fox, A.D., Desholm, M., Kahlert, J., Christensen, T.K. & Petersen, I.K. (2006) Information needs to support environmental impact assessment of the effects of European offshore wind farms on birds. *Ibis*, **148**, 129–144.
- Johnston, A., Cook, A.S.C.P., Wright, L.J., Humphreys, E.M. & Burton, N.H.K. (2014) Modelling flight heights of marine birds to more accurately assess collision risk with offshore wind turbines. *Journal of Applied Ecology*, **51**, 31–41.
- Langston, R.H.W. (2013) Birds and wind projects across the pond: A UK perspective. *Wildlife Society Bulletin*, **37**, 5–18.
- McAdam, B.J. (2005) *A Monte-Carlo Model for Bird / Wind Turbine Collisions*. MSc Ecology. University of Aberdeen.
- Tucker, V.A. (1996) A mathematical model of bird collisions with wind turbine rotors. *Journal of Solar Energy Engineering*, 253–262.

Appendix 1: Stakeholder Interviews

Purpose of interviews

To obtain views and opinions of a wide range of stakeholders involved in offshore wind, on collision risk models and modelling, particularly in relation to uncertainty and variability.

Interview questions

Conducted telephone interviews based around the following questions:

1. How much experience do you have, relating to collision risk models/modelling?
2. What collision risk models do you most regularly use or have experience of?
3. What uncertainties exist in the collision risk models that you have used?
4. What are the key uncertainties in input parameters?
5. What parameters do you think have the greatest influence on the outputs of collision risk modelling?
6. If you could, how would you improve collision risk models/modelling?
7. Would the explicit reporting of variability and uncertainty in outputs from collision risk models benefit the consenting process and discussions with regulators?

Interviews were approximately 20-30 minutes each.

Interviewees

I contacted 30 people from a range of stakeholder groups and from those I conducted 20 interviews with people from the following organisations:

BTO	CEH
DONG Energy	ECON
EDPR	Joint Nature Conservation Committee
MacArthur Green	Marine Scotland Science
Natural England	Natural Power
NIRAS	Pelagica
PMSS	Royal Society for the Protection of Birds
Scottish Natural Heritage	Statkraft/Forewind
Sue King Consulting	The Crown Estate
	...and Bill Band

Results

Experience of interviewees

Question 1: How much experience do you have, relating to collision risk models/modelling?

The experience of interviewees varied from 'intelligent client' to model creator. All interviewees had a good understanding of the general modelling process and the use of model output though not all had conducted the modelling and run the models themselves. One person declined the offer of being interviewed because they thought they didn't have enough experience to contribute constructively.

Question 2: What collision risk models do you most regularly use or have experience of?

All people interviewed (20) used the Band model and the associated updates. Of these, most people mentioned options 1 and 3 rather than 2 and 4. Additionally, 5 people used the Folkerts model, though less regularly, and one had an understanding of the Tucker model. These were the only models mentioned.

Uncertainties in collision risk modelling

Question 3: What uncertainties exist in the collision risk models that you have used?

This question was targeted at the broader uncertainties surrounding collision risk modelling. The following opinions were given more than once:

- Data collection methods including number and timing of surveys and the fact that surveys only occur in good weather least to a density estimate which may not capture the variability in the environment.
- The use of the Rochdale Envelope and therefore wide ranges for turbine parameters.
- How much precaution should be included?
- Bird behaviour and avoidance
- Which option of the model (or in most cases, which option of Band) is acceptable?
- Little empirical data and also no validation or comparison with post-construction data.
- The appropriate use of the model and output. The collision estimate is considered as definitive and black and white when it is supposed to be a collision risk tool.
- In the case of the Band model, what is the latest version of the model and flight height data sets to use?

Question 4: What are the key uncertainties in input parameters?

All of the input parameters were discussed and raised by the interviewees as a whole but those that occurred more than once and in descending order (most frequently highlighted first):

- Flight height data
- Avoidance
- Density
- Nocturnal activity
- Flight speed
- Rotor speed

Question 5: What parameters do you think have the greatest influence on the outputs of collision risk modelling?

Most of the input parameters were discussed and raised by the interviewees as a whole but those that occurred more than once and in descending order (most frequently highlighted first):

- Avoidance rate
- Flight height data
- Rotor Speed
- Density
- Number of turbines
- Which Band option used
- Operation time

Changes or updates to model

Question 6: If you could, how would you improve collision risk models/modelling?

There were many different opinions on how to improve collision risk modelling but generally they did not involve making large changes to the mechanics of the model itself but rather to the input data or presentation of data and outputs. Comments that were raised more than once and in descending order (most frequently highlighted first) included:

- Present a covering/summary sheet with input data values to ensure parameters are clearly set out and defined.
- Stop presenting single numbers as black and white and also provide context.
- Take data from existing sites to validate the model and also use post-construction monitoring.
- Have a standard approach to derive turbine parameters and bird parameters including consistently defining breeding season periods.
- More studies/data on bird behaviour around turbines and avoidance behaviour.

- More and clearer guidance on the model and model use and intended use, especially on the tidal offset.
- Collect flight height data objectively, not just human observation/estimation but using rangefinders.
- Factor uncertainty into estimates.
- Use R code rather than excel to make modelling process more reproducible.
- Better interpretation of model outputs.
- Single location to have the most up to date version of model and email updates.

These can then be split into comments that were more input data-related:

- Present a covering/summary sheet with input data values to ensure parameters are clearly set out and defined.
- Have a standard approach to derive turbine parameters and bird parameters including consistently defining breeding season periods.
- More studies/data on bird behaviour around turbines and avoidance behaviour.
- Collect flight height data objectively, not just human observation/estimation but using rangefinders.

Or those which were model or output data-related:

- Stop presenting single numbers as black and white and also provide context.
- Take data from existing sites to validate the model and also use post-construction monitoring.
- More and clearer guidance on the model and model use and intended use, especially on the tidal offset.
- Factor uncertainty into estimates.
- Use R code rather than excel to make modelling process more reproducible.
- Better interpretation of model outputs.
- Single location to have the most up to date version of model and email updates.

Question 7: Would the explicit reporting of variability and uncertainty in outputs from collision risk models benefit the consenting process and discussions with regulators?

When asked more specifically about including variability and uncertainty in CRMs interviewees gave a wide range of responses but these were not consistent within different stakeholder groups. Of the 20 people interviewed, 13 agreed that including variability and uncertainty in outputs from collision risk models would benefit the consenting process and discussions with regulators, however 7 people disagreed. Of those 7, all said that they disagreed because of the consenting and assessment process and that in principle it would be better to include variability and uncertainty, but they thought that the system did not allow for it. A recurrent comment was that interviewees were unsure of how variability and uncertainty could be included in outputs and still fit in with the Habitats Regulations.

Some comments and themes that were raised in the interviews are listed below:

- Scientifically there is a benefit to making clear what the uncertainties are.
- Accounting for uncertainty in data collection methods and survey data would be useful.
- I am uncomfortable with presenting a value that is apparently so precise.
- There is an absolute fixation on single numbers which is dangerous.
- We need greater acceptance that we live and work in an uncertain world and things are grey, not black and white.
- We need a way of showing that some scenarios are more likely than others.
- Decision makers have to be confident that they are making the right decisions so they need to an understanding of uncertainty around the single numbers.
- We need to weigh up risk (or use a risk assessment process) and we can't do that currently with CRM, though it happens more regularly with PVA.
- The current approach is too precautionary and always uses the most precautionary values.
- If the system were to change, including variability and uncertainty is a more useful approach.
- Any outputs need to be suitable to be taken forward through the assessment process.
- The risk is that it complicates the process even more than already because the more the risks are explicit the more difficult it is to explain to the planning inspectorate.
- There is probably too much uncertainty in the system to make it useful to include it.

There was a wide range of views on some topics, for example opinions on using probability distributions:

- Presenting probability distributions would help a lot because regulators often have a background of understanding risk probabilities.
- Using probability distributions might help with presentation but it might not help with interpretation of outputs, especially if people don't understand how to interpret probability distributions.
- Distributions are probably more helpful but people need to understand them.
- Scientists are used to dealing with probabilities but legislation is binary.

This probably stems from uncertainty and/or inconsistency in (the understanding of) how decisions are made and the lack of a strategic decision on a standard method for presenting data which is most informative for the decision makers.

Appendix 2: Sensitivity analyses

Chamberlain *et al.* (2006) previously documented that the Band model was sensitive to input parameters. Following on from this, the sensitivity of the Band model update produced during the SOSS project (Band 2012) was assessed, both for the basic and extended versions. Similar to Chamberlain *et al.* (2006), the effect of a 10% change in the input parameters was assessed but in addition, a more realistic parameter range was also assessed.

When assessing the effect of a 10% change in the flight height distribution for the extended model, we increased the proportions of birds at heights between the minimum and maximum rotor tip heights by 10%.

The following data sources were used for the input parameters. For turbine-related parameters, expert opinion within the project group was used to assess reasonable parameters ranges and those likely to be built out in the near future.

Bird-related Parameter	Data description
Length	Taken from Concise Birds of the Western Palearctic (Cramp and Perrins, 1993) and other sources
Wingspan	Taken from Concise Birds of the Western Palearctic (Cramp and Perrins, 1993) and other sources
Flight speed	RSPB telemetry data (breeding season only)
Nocturnal activity	RSPB telemetry data (breeding season only)
Proportion at collision risk height	Generic flight height curve provided with the Band model and data provided by BTO (Johnston <i>et al.</i> 2014).
Flight height distributions	Data provided by BTO (Johnston <i>et al.</i> 2014).
Avoidance	'All gulls' rate available from Marine Scotland Science avoidance report (Cook <i>et al.</i> 2014)
Bird density	Taken from Creyke Beck A Environmental Statement

Turbine-related Parameter	Description/Notes
Rotor radius	Expert opinion
Hub height	Expert opinion
Max. blade chord width	Expert opinion
Rotation speed	Expert opinion (example relationship between wind speed and rotation speed)
Blade pitch	Expert opinion (example relationship between wind speed and pitch)
Turbine operation time	Taken from Inch Cape Environmental Statement

10% change

BASIC MODEL (Option 1)

Input variable	Baseline	Baseline ± 10% (increases mortality)	Collision risk (in absence of avoidance)	Revised number of collisions	% increase in number of collisions
Avoidance rate	0.9893	0.8904	0.065	439	921
Non-avoidance rate	0.0107	0.0118	0.065	47	9
% at collision risk height	6	6.6	0.065	47	9
Bird density (birds/km²)	9.89	10.879	0.065	47	9
Flight speed (m.s⁻¹)	7.26	7.986	0.063	46	7
% nocturnal flight	3.3	3.63	0.065	43	0
Bird length (cm)	39	42.9	0.067	44	2
Wing span (cm)	108	118.8	0.065	43	0
Number of turbines	100	110	0.056	47	9
Rotor radius (m)	80	88	0.061	44	2
Hub height (m)	125	112.5	0.065	43	0
Rotation speed (rpm)	7.74	8.514	0.067	44	2
Blade width (m)	5.5	6.05	0.069	46	7
Blade pitch (degrees)	0	-	-	-	-
% time operational	87.61	96.371	0.065	47	9

Effects of 10% variation in input parameters on predicted mortality rates of black-legged kittiwakes using hypothetical wind farm parameters (100 turbines). Original collision risk was 0.065 and the original number of predicted collisions per year was 43.

Collisions are presented as integers.

EXTENDED MODEL (Option3)

Input variable	Baseline	Baseline \pm 10% (whichever increases mortality)	Collision risk (in absence of avoidance)	Revised number of collisions	% increase in number of collisions
Avoidance rate	0.9672	0.8705	0.065	9	350
Non-avoidance rate	0.0328	0.0361	0.065	3	50
% at collision risk height	6	6.6	0.065	3	50
Bird density (birds/km ²)	9.89	10.879	0.065	3	50
Flight speed (m.s ⁻¹)	7.26	7.986	0.063	2	0
% nocturnal flight	3.3	3.63	0.065	2	0
Bird length (cm)	39	42.9	0.067	2	0
Wing span (cm)	108	118.8	0.065	2	0
Number of turbines	100	110	0.065	3	50
Rotor radius (m)	80	88	0.061	5	150
Hub height (m)	125	112.5	0.065	8	300
Rotation speed (rpm)	7.74	8.514	0.067	2	0
Blade width (m)	5.5	6.05	0.069	2	0
Blade pitch (degrees)	0	-	-	-	-
% time operational	87.61	96.371	0.065	3	50


Effects of 10% variation in input parameters on predicted mortality rates of black-legged kittiwakes using the hypothetical wind farm parameters (100 turbines). The original collision risk was 0.065 and the original number of predicted collisions per year was 2. Collisions are presented as integers, therefore the % increase in the number of collisions is greatly influenced by rounding.

Real data range

BASIC MODEL (Option 1)

Input variable	Input variability	Mean collisions (SD)	Median collisions (IQR)
Avoidance rate	N(0.9893,0.0007)	39.76 (2.55)	39.72 (3.61)
% at collision risk height	N(6, 0.9)	39.77 (6.06)	39.77 (7.86)
Bird density (birds/km²)	tN(monthly mean, monthly SD)	41.86 (6.40)	41.99 (8.39)
Flight speed (m.s⁻¹)	N(7.26, 1.50)	40.25 (5.73)	40.30 (8.09)
% nocturnal flight	N(3.3, 0.45)	39.90 (0.19)	39.91 (0.26)
Bird length (cm)	N(39, 0.5)	39.89 (0.15)	39.89 (0.21)
Wing span (cm)	N(108, 4)	39.89 (0.09)	39.89 (0.12)
Rotor radius (m)	N(80, 5)	39.89 (0.67)	39.84 (0.88)
Hub height (m)	Rotor radius + N(26.5, 2)	39.89 (0)	39.89 (0)
Rotation speed (rpm)	Relationship to wind speed	40.15 (1.81)	38.51 (3.76)
Blade width (m)	N(5.5,0.3)	39.91 (1.39)	39.90 (1.97)
Blade pitch (degrees)	Relationship to wind speed	40.50 (1.66)	39.89 (0.32)
% time operational	Wind availability-tN(6.3, 2)	39.91 (1.39)	39.90 (1.97)

Effects of variation in input parameters on predicted mortality rates of black-legged kittiwakes using the hypothetical wind farm parameters (100 turbines). 500 iterations. The original collision risk was 0.065 and the original number of predicted collisions per year was 40. N is normal distribution. N(mean, SD). tN is truncated normal distribution. Hub height does not affect calculations in option 1, therefore the values were constant across all iterations.




Effects of variation in input parameters on predicted collision mortality of black-legged kittiwakes using the basic Band model. Density values are slightly skewed due to need for use of truncated normal distribution as negative density values are not possible.

EXTENDED MODEL (Option3)


Input variable	Input variability	Mean collisions (SD)	Median collisions (IQR)
Avoidance rate	N(0.9672, 0.0018)	18.34(1.03)	18.33 (1.35)
% at collision risk height	Data from BTO	29.60 (5.92)	29.94 (7.70)
Bird density (birds/km²)	tN(monthly mean, monthly SD)	19.06 (3.03)	18.97 (4.04)
Flight speed (m.s⁻¹)	N(7.26, 1.50)	18.31 (1.38)	18.32 (1.75)
% nocturnal flight	N(3.3, 0.45)	18.32 (0.09)	18.32 (0.12)
Bird length (cm)	N(39, 0.5)	18.32 (0.16)	18.32 (0.22)
Wing span (cm)	N(108, 4)	18.32 (0.16)	18.32 (0.22)
Rotor radius (m)	N(80, 5)	18.35 (0.10)	18.13 (0.14)
Hub height (m)	Rotor radius + N(26.5, 2)	18.72 (5.33)	18.11 (7.08)
Rotation speed (rpm)	Relationship to wind speed	18.57 (1.87)	16.86 (3.89)
Blade width (m)	N(5.5,0.3)	18.31 (0.32)	18.32 (0.44)
Blade pitch (degrees)	Relationship to wind speed	18.32 (0.00074)	18.32 (0.00014)
% time operational	Wind availability-tN(6.3, 2)	18.32 (0.14)	18.32 (0.18)

Effects of variation in input parameters on predicted mortality rates of black-legged kittiwakes using the hypothetical wind farm parameters (100 turbines). 500 iterations. The original collision risk was 0.065 and the original number of predicted collisions per year was 18. N is normal distribution. N(mean, SD). tN is truncated normal distribution.




Effects of variation in input parameters on predicted collision mortality of black-legged kittiwakes using the extended Band model. Density values are slightly skewed due to need for use of truncated normal distribution as negative density values are not possible.

A note on variation in flight height: It is noticeable that when variation in the flight height distribution used for the extended model (option 3) is considered, it results in a very different average value to that obtained using the best fit distribution. This should be expected. Flight height distributions are estimated following the methodology set out in Johnston et al. (2014). The best fit distribution is estimated from the complete flight height dataset, and is that which best fits the available data. Confidence intervals were calculated around this distribution using a bootstrapping approach, randomly sampling from the original dataset each time. As a result, each individual bootstrap reflects the shape of the distribution would be if some of the data were excluded. It is not meaningful to compare the mean values obtained from the bootstraps to the best-fit distribution because they are a series of sub-samples. On closer examination, it is clear that the best fit distribution predicts a lower proportion of birds at collision risk height than is obtained from the mean across all bootstraps, and that crucially, this difference is greatest towards the centre of the rotor-swept area, where collision risk is greatest. As a result, the mean collision rate predicted from the bootstraps is greater than collision rate predicted from the best fit distribution.



Comparison of the best fit (red) and bootstrapped (grey) flight height distributions for kittiwake. The best fit distribution does not pass through the centre of the bootstrapped distributions as would be expected if it were directly comparable to the mean. Instead, as height above sea level increases, the proportion of birds predicted by the best-fit distribution moves towards the lower end of the proportion predicted by the bootstraps. The difference is most apparent at heights of around 100 m, which roughly corresponds to the centre of the rotor sweep, the point at which collision risk is greatest. This can be seen more clearly by examining the ratio of the best fit distribution to the mean of the bootstrap distribution at 1 m intervals.





© Crown copyright 2015

OGL

This publication is licensed under the terms of the Open Government Licence v3.0 except where otherwise stated. To view this licence, visit nationalarchives.gov.uk/doc/open-government-licence/version/3 or write to the Information Policy Team, The National Archives, Kew, London TW9 4DU, or email: psi@nationalarchives.gsi.gov.uk.

Where we have identified any third party copyright information you will need to obtain permission from the copyright holders concerned.

This publication is available at www.scotland.gov.uk

Any enquiries regarding this publication should be sent to us at
The Scottish Government
St Andrew's House
Edinburgh
EH1 3DG

ISBN: 978-1-78544-680-1- (web only)

Published by The Scottish Government, September 2015

Produced for The Scottish Government by APS Group Scotland, 21 Tennant Street, Edinburgh EH6 5NA
PPDAS56549 (09/15)

W W W . G O V . S C O T